

SONIFEX

RB-DDA6A-2P

6 Way Stereo AES/EBU Digital Distribution Amplifier with
Dual Power Supplies

Catalogue





RB-DDA6A-2P 6 Way Stereo AES/EBU Digital Distribution Amplifier with Dual Power Supplies

The RB-DDA6A-2P digital distribution amplifier is used for distributing digital audio data in AES/EBU format, repeating both the audio data and the status information of the input whilst re-normalising to standard digital audio levels.

It has a single XLR-3 female AES/EBU audio input which is distributed to 6 XLR-3 male AES/EBU outputs.

Applications include distributing audio from a digital mixing desk to multiple digital

recorders, or feeding multiple studios with an output from a flashcard player.

It can accept input sample rates in the range of 30kHz - 100kHz, and bit rates of 16, 20 and 24 bit. So, it can be used for standard CD signal distribution at 16 bit 44.1kHz, as well as for high quality 24 bit 96kHz recording.

The unit provides redundancy protection by using two power supply units that can be supplied from separate mains feeds. The

unit automatically load shares between the two supplies so that if either supply should fail the unit will continue to work correctly. If both supplies fail the input is connected directly to output 1.

The condition of the two supplies is indicated on the front panel by two red LEDs which illuminate to indicate the correct function of the supply. On the alarm output connector there is a changeover relay to indicate the status of each supply. This is normally closed to indicate power fail and once the supply is working correctly the relay activates to make a normally open contact.

Specification For RB-DDA6A-2P

Audio Specification	
Input Impedance:	110Ω ±20% balanced
Output Impedance:	110Ω ±20% balanced
Sample Freq Range:	30-100kHz (i.e. including 32kHz, 44.1kHz, 48kHz, 64kHz, 88.2kHz and 96kHz)
Signal Level:	2V/7V peak to peak min/max
Connections	
Audio Inputs:	1 x AES/EBU XLR 3 pin female (balanced)
Audio Outputs:	6 x AES/EBU XLR 3 pin male (balanced)
Alarm Outouts:	2 x Relay output indicators on 1 x 9 pin D-Type socket
Mains Input:	2 x Filtered IEC, 85-264V switchable, fused, 6W max
Fuse Rating:	2 x Anti-surge fuse 1A 20 x 5mm
Equipment Type	
RB-DDA6A-2P:	6 way AES/EBU stereo digital distribution amplifier with dual power supplies
Physical Specification	
Dimensions (Raw):	48cm (W) x 10.8cm (D) x 4.2cm (H) (1U) 19" (W) x 4.3" (D) x 1.7" (H)(1U)
Dimensions (Boxed):	58.5cm (W) x 22.5cm (D) x 7cm (H) 23" (W) x 8.9" (D) x 2.8" (H)
Weight:	Nett: 1.5kg Gross: 2.0kg Nett: 3.3lbs Gross: 4.4lbs



SONIFEX

www.sonifex.co.uk

UK Office:

Sonifex Ltd

61 Station Road, Irthlingborough,

Northants, NN9 5QE, UK

Tel: +44 (0) 1933 650700

Fax: +44 (0) 1933 650726

Email: sales@sonifex.co.uk

Australian Office:

Sonifex Pty Ltd

12/6 Leighton Place,

Hornsby NSW 2077, Australia

Tel: +61 (2) 9987 0499

Fax: +61 (2) 9476 4950

Email: sales@sonifex.com.au