

SONIFEX

RB-DHD6

Digital 6 Way Stereo Headphone Distribution Amplifier

Catalogue





RB-DHD6 Digital 6 Way Stereo Headphone Distribution Amplifier



Category: Headphone Distribution Amplifiers.

Product Function: Distributes a stereo digital line level signal to 6 x headphone outputs.

Typical Applications: Provides multiple guest headphone outputs from the digital output of a radio mixer or router matrix.

Features: Individual volume controls, AES/EBU or S/PDIF input switch.

The RB-DHD6 digital 6 way headphone distribution amplifier is a 1U rack-mount which receives a digital input signal, as either AES/EBU or S/PDIF and converts it to 6 individually buffered, jack-plug, headphone outputs, each with their own volume control.



Useful for connection to digital mixing desks, digital routers and matrices, the RB-DHD6 connects directly to an AES/EBU or S/PDIF output to provide the highest quality audio directly to the headphones.

The input connectors consist of a single balanced XLR-3 for the AES/EBU input and a single unbalanced phono connector for the S/PDIF input.

A button located on the rear panel is used to select either the AES/EBU, or S/PDIF, input and de-emphasis on the output can be controlled via dipswitch.

If de-emphasis is selected, the RB-DHD6 will decode 50/15µs emphasis when indicated by certain channel status bits in the incoming digital audio data.

When operating, the front panel power LED flashes red and amber whenever the unit is not synchronised to the incoming digital signal.

Specification For RB-DHD6

Audio Specification

Output Level:	Drives 150mW into 32Ω to 600Ω headphones
Dynamic Range:	>100dB
Input Impedance:	110Ω ±20% AES/EBU 75Ω ±15% S/PDIF
Maximum Output Level:	+12dBu unbalanced
Headphone Gain Range:	-80dBu to +12dBu
Sample Frequency Range:	30kHz-100kHz
Connections	
Digital Inputs:	1 x AES/EBU XLR 3 pin female, 1 x S/PDIF RCA phono
Headphone Outputs:	6 x ¼" (6.35mm) A/B-gauge 3-pole stereo jack sockets
Mains Input:	Filtered IEC, 110V-120V, or 220-240V, fused, 10W max

Fuse Rating:	Anti-surge fuse 100mA 20 x 5mm (230VAC) Anti-surge fuse 250mA 20 x 5mm (115VAC)
--------------	------------------------------------------------------------------------------------

Operational Controls

De-emphasis On/Off:	DIP switch selection
Digital Input Select:	AES/EBU or S/PDIF, via push-switch

Equipment Type

RB-DHD6:	Digital 6 way stereo headphone distribution amplifier
----------	-------------------------------------------------------

Physical Specification

Dimensions (Raw):	48cm (W) x 10.8cm (D) x 4.2cm (H) (1U) 19" (W) x 4.3" (D) x 1.7" (H) (1U)
Dimensions (Boxed):	58.5cm (W) x 22.5cm (D) x 7cm (H) 23" (W) x 8.9" (D) x 2.8" (H)
Weight:	Nett: 1.6kg Gross: 2.2kg Nett: 3.5lbs Gross: 4.8lbs

SONIFEX

www.sonifex.co.uk

UK Office:

Sonifex Ltd

61 Station Road, Irthlingborough,

Northants, NN9 5QE, UK

Tel: +44 (0) 1933 650700

Fax: +44 (0) 1933 650726

Email: sales@sonifex.co.uk

Australian Office:

Sonifex Pty Ltd

12/6 Leighton Place,

Hornsby NSW 2077, Australia

Tel: +61 (2) 9987 0499

Fax: +61 (2) 9476 4950

Email: sales@sonifex.com.au